



高雄贸易有限公司

KAOH SIUNG TRADING SDN. BHD.



## *Direct Heat Sealer / Constant Heat Sealer*

Direct Heat Sealer (also known as Constant Heat Sealers) are equipped with a thermostat or an electronic thermostat controller that accurately controls the temperature from 30°-550° F (0°-300° C). Depending on the heat sealers model a constant heat sealer can seal material up to 15mm in width and 8 mil in thickness. Direct Heat Sealer with constant heat controller maintain constant heat in both of the device's jaws to provide better heat penetration when sealing thicker materials and create wide seals on heavier bags.

Direct Heat Sealer are a specialty sealer that is not for the common use of bag sealing operations, but especially ideal for thicker material such as coated aluminium foil, Kraft paper, cellophane, mylar, coated PP.

## *CFN Series Constant Heat Sealer*

CFN Series Constant Heat Sealer are excellent for sealing polycell films, humidity-proof cellophane film, polyethylene film, aluminium foil coated bags and gusset bags. CFN Series able to create mesh seal or line seal upon sealing.

CFN Series Constant Heat Sealer is equipped with a temperature controller complete with pedestal, stand, adjustable work table and foot control.. CFN Series has been injection mould cast and electro static painted for durability.



### TECHNICAL DATA

<b>◀ MODEL</b>		<b>400CFN</b>
Voltage		1 Phase 240V
Sealing Power		420 W
Sealing Length		400 mm
Sealing Width	Line	10 mm
	Mesh	15mm
Sealing Jaw		Top & Bottom
Heat Time Setting		80 - 250°C
Machine Structure		Die-Cast with powder coat
Machine Dimension		470mmL x 520mmD x 1000mmH
Machine Weight		31Kg