



高雄贸易有限公司

KAOH SIUNG TRADING SDN. BHD.



Induction Sealing Machine

Induction Sealing Machine also known as Aluminium Foil Sealing Machine is the perfect machine to hermetically seal with aluminium foil all types of products (except metal bottles) to prevent leakage, contamination, and mildew formation, and to extend the shelf-life of any kind of product. The induction sealer transmits electromagnetic energy which is received by the aluminium foil liner causing it to heat up and weld itself across the container neck. Works on various types of plastic laminated (composite) aluminium foils such as PE, PP, PET & PVC.

Induction Sealer commonly use for products from pharmaceuticals to food and industries. Induction sealing applies to liquid products like beverages and automotive oil, and dried products like pharmaceuticals medicine, food powders and dry grain products in container.

Automatic Induction Sealer

SF2300 Series Automatic Induction Sealer utilizes electro magnetic induction principle to produce instant high heat to melt aluminium foil to seal bottles. SF2300 Series Automatic Induction Sealer is design for attachment on high speed production. SF2300 Series complete with roller which flexible to relocate to different production line.

SF2300 Series Induction Sealer have two difference model: SF2300S sealing diameter range 15mm - 60mm; SF2300L sealing diameter range 50mm - 120mm.

Optional : a. Extend Adjustable Height range as requested; b. Conveyor



TECHNICAL DATA

MODEL	SF2300S	SF2300L
Voltage	1 Phase 240V	
Max. Power	4000 W	
Sealing Diameter	15mm - 60mm	50mm - 120mm
Operate Model	Automatic	
Adjustable Height from Conveyor to Sealing Head	750mmH - 1100mmH	
Sealing Speed	0 - 230 bottle /min	
Cooling Method	Fan Air Cooling	
Machine Structure	Stainless Steel	
Machine Weight	50 Kg	
Machine Dimension	1050mmL x 480mmW x 1115mmH	