



高雄贸易有限公司

KAOH SIUNG TRADING SDN. BHD.



Vacuum Packaging Machine - External Type

External Vacuum Packaging Machine involve a bag being attached to the vacuum-sealing machine externally. The machine will remove the air and seal the bag, which is all done outside the machine. Nozzle type vacuum sealers provide flexibility and fast vacuuming. Gas flushing is also available in nozzle type vacuum sealers selection. High performance impulse sealing system is built into the vacuum sealers.

External Vacuum Packaging Machine is commonly use in Industry such as electronic or medical use vacuum packing for Electronic parts, hardware products, medical instruments, medicine to prevent oxidization or dust. In clothing, bedding and plastic industry vacuum packing greatly to compress the packing size items for more storage space and save logistic cost. For delicate food items which might be crushed by the vacuum packing process (such as potato chips), an alternative is to replace the interior gas with nitrogen to retain the freshness of products or prevent from crash. This has the same effect of inhibiting deterioration due to the removal of oxygen.

** Customized specification available upon request.

VSC-TP Series Table Top Digital Vacuum Sealer - Pneumatic

VSC-TP Series with table top designed external vacuum sealer for special for factory with limited working area. VSC-TP series using pneumatic system to complete the vacuum and sealing of packaging. It's control system is powered by PLC controller and Touch Screen Panel (HMI) for precise settings and user-friendly operations.

** Customized specification available upon request.



TECHNICAL DATA

Model	KST-VSC450TP	Model	KST-VSC450TP
Sealing Length	450 mm	Control Panel	Touch Screen
Sealing Width	10mm	Heat Time	0.2 - 2.5 sec
Sealing Thickness	2 X 0.15mm / 0.4mm	Cooling Time	0 - 10 sec
Sealing Jaw	Single Jaw - Bottom Only	Voltage	1 Phase 240V
Ultimate Vacuum Pressure (Kpa)	0.2	Sealing Power	1000 W
No. of Nozzle	Single or Double	Air Pressure	> 0.6 Mpa (6 bar)
Vacuum / Inflate Time	0 - 30 sec	Machine Structure	Stainless Steel
Vacuum Operation	Vacuum Generator	Machine Weight	45 Kg
Jaw Operate	Pneumatic Cylinder	Machine Dimension	520mmL x 400mmW x 480mmH