



高雄贸易有限公司

KAOH SIUNG TRADING SDN. BHD.



Vacuum Packaging Machine - External Type

External Vacuum Packaging Machine involve a bag being attached to the vacuum-sealing machine externally. The machine will remove the air and seal the bag, which is all done outside the machine. Nozzle type vacuum sealers provide flexibility and fast vacuuming. Gas flushing is also available in nozzle type vacuum sealers selection. High performance impulse sealing system is built into the vacuum sealers.

External Vacuum Packaging Machine is commonly use in Industry such as electronic or medical use vacuum packing for Electronic parts, hardware products, medical instruments, medicine to prevent oxidization or dust. In clothing, bedding and plastic industry vacuum packing greatly to compress the packing size items for more storage space and save logistic cost. For delicate food items which might be crushed by the vacuum packing process (such as potato chips), an alternative is to replace the interior gas with nitrogen to retain the freshness of products or prevent from crash. This has the same effect of inhibiting deterioration due to the removal of oxygen.

** Customized specification available upon request.

VSC-VA Series Vertical Type Digital Vacuum Sealer - Motor

VSC-V Series is a external vacuum sealer with vertical designed. VSC-V Series special design to pack large products which unable to fold or lay down vertically such as rice, huge grain packing. VSC-VA Series complete with a automatic lifting system to adjust the sealing height. It's control system is powered by PLC controller and Touch Screen Panel (HMI) for precise settings and user-friendly operations.



TECHNICAL DATA

Model	KST-VSC800VA
Sealing Length	800mm
Sealing Width	10mm
Sealing Thickness	2 X 0.15 / 0.4 mm
Max. Packing Size	800mmL x 600mmW x 920mmH
Sealing Jaw	Single Jaw Only
Sealing Jaw Operation	Pneumatic Cylinder
No. of Nozzle	Single or Double
Height Adjustment	Automatic
Height Adjust Operation	Pneumatic Cylinder
Vacuum Operation	900W Vacuum Pump
Vacuum / Inflate Time	0 - 30 sec
Ultimate Vacuum Pressure (Kpa)	0.2
Control Panel	Touch Screen
Heat Time	0 - 2 sec
Cooling Time	0 - 10 sec
Voltage	1 Phase 240V
Sealing Power	2200W
Machine Structure	Stainless Steel
Machine Weight	100kg
Machine Dimension	870mmL x 820mmW x 1680mmH