



高雄贸易有限公司

KAOH SIUNG TRADING SDN. BHD.



Semi Automatic Double Heat Impulse Sealer

Semi Automatic Double Heat Impulse Sealers designed with two heating jaw (top and bottom) able to seal up to 18mil gusseted or regular thermoplastic film. Semi Automatic Double Impulse Sealers is best for all sealing purposes and recommended for a variety of other common thermoplastic materials including : Polyethylene, Polyurethane, Polyvinylchloride, Polyvinyl Alcohol, Nylon, bubble packs, padded mailers, foil, coated bags and etc.

Semi Automatic Double Heat Impulse Sealers are easy to use (no warm-up time), economical (electricity is only used when the jaw is lowered during the sealing process), and safe (no component of these devices is always hot) which is ideal for sealing operations in packaging candies, food, stationery, drugs, tools, replacement parts and a variety of other products.

FSA Series Temperature Control Impulse Sealer

FSA Series Semi Auto Impulse Sealer are equipped with a temperature control system that accurately controls the temperature to control each seal quality. FSA Series is table top heavy duty sealing machine designed with two heating jaw (top and bottom) are heated simultaneously resulting in better heat penetration to seal thicker material. Two difference sealing length is available: 450mm and 600mm with 5mm sealing width.

FSA Series Semi Auto Impulse Sealers is table top heavy duty sealing machine designed with two heating jaw (top and bottom) able to seal up to 18mil gusseted or regular thermoplastic film. This sealer is best for all sealing purposes. Foot switch included for manual operation.

Optional: a. 10mm Sealing Width



TECHNICAL DATA

MODEL	445 FSA	605 FSA
Special Features	Digital Temperature Setting Control	
Voltage	1 Phase 240V	
Sealing Power	1900 W	2300 W
Sealing Length	450 mm	600 mm
Sealing Width	5 mm	
Sealing Jaw	Top & Bottom	
Heat Time Setting	0 - 2 sec	
Cooling Time Setting	0 - 4 sec	
Machine Structure	Die-Cast with powder coat	
Machine Dimension	520mmL x 520mmD x 400mmH	660mmL x 520mmD x 400mmH
Machine Weight	22Kg	23Kg