



高雄贸易有限公司

KAOH SIUNG TRADING SDN. BHD.



Semi Automatic Impulse Sealer

Semi Automatic Pneumatic Impulse Sealer adopts with pneumatic cylinder required compressed air as motive power with adjustable sealing pressure and double heating sealer for reliable sealing quality.

Semi Automatic Pneumatic Impulse Sealer commonly used in the fields of animal feed, chemicals, aggregates, food, fertilizer, detergents, pet food, spices, sugar, grains and cereals, insulation, pellets, powders, etc.

SCP Series Digital Semi Automatic Pneumatic Impulse Sealer

SCP Series Digital Semi Automatic Pneumatic Impulse Sealer is sealing machine equipped with pneumatic cylinder. Design with bottom jaw sealing is suitable for sealing various plastic film bags with sealing length of 1000mm / 1500mm and 10mm sealing width.

SCP Series Digital Semi Automatic Pneumatic Impulse Sealer control system is powered by PLC controller and Touch Screen Panel (HMI) for precise settings and user-friendly operations. SCP Series design adopts with pneumatic cylinder required compressed air as motive power with adjustable sealing pressure and separate programmable timers for heating, congealing and recycling for different material thickness. Once correct setting have been programmed, consistent seals and cooling are maintained automatically for perfect sealing quality.

** Customized specification available upon request.



TECHNICAL DATA

Model	KST-SCP1000	KST-SCP1500
Sealing Length	1000mm	1500mm
Sealing Width	10mm	
Sealing Thickness	2 X 0.15 / 0.4 mm	
Sealing Jaw	Bottom Only	
Sealing Jaw Operation	Pneumatic Cylinder	
Control Panel	Touch Screen	
Heat Time	0 - 2 sec	
Cooling Time	0 - 10 sec	
Voltage	1 Phase 240V	
Sealing Power	3500 W	
Air Compressor (prepare by customer)	0.4 - 0.6 Mpa	
Machine Structure	Stainless Steel	
Machine Weight	104kg	
Machine Dimension	1520mmL x 560mmD x 1050mmH	